

3PH – 1PH ONLINE UPS

Specifications	
Model	ARP 310
Rating	10KVA to 80KVA
AC INPUT	415V + 15% -15%, Three Phase Input
Frequency	50Hz ± 6%
DC VOLTAGE:	360/384VDC
Charging Time	12 Hours for 90% of full Capacity
Charger Type	CVCC (Constant Current Constant Voltage type)
INVERTER:	
Technology	DSP based, IGBT Switching
Output Voltage	230V AC Three Phase
Voltage Regulation	± 1%
Frequency	50Hz ± 0.1Hz
Waveform	PWM Sine wave
Harmonic Distortion	Less than 3% on Linear Load
Inverter Efficiency	Upto 90% till 30KVA and upto 93% above 30KVA
Power Factor	0.8
Overload	110 % for 5 min, 150% for 30 sec
Crest Factor	3:1
Audible Noise	Less than 65 dB at 1 Meter
DISPLAY :	
Digital LCD Display for	Output Voltages, Output current & Frequency, DC Voltage, Battery and Load Percentage and All Faults
INDICATIONS & ALARMS:	
a) Mains on	LED Indication
b) Inverter	LED Indication
c) Batt Low	LED Indication & Alarm
d) Fault	LED Indication & Alarm
e) Overload	LED Indication & Alarm
GENERAL:	
Operating temperature	0°C to 40°C
Humidity	Max 95%, Non-condensing
PROTECTIONS :	Output Overload & Short circuit, Output UV & OV, DC Under & Overvoltage, Mains Under & Overvoltage, Mains Single Phasing
OPTIONAL :	
Communication	SNMP
Bypass	Static Switch

*Specifications are subject to change without prior notice due to constant improvement in design & technology

*Specification can be customized to suit specific requirement